

ENBS GLS RWY 03 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ERNIX	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	MIKDU	-	-	-16.0	5.0	-	-	A4000+	-	-	-	1.0
010	IF	BITBO	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	MIKDU	-	-	-16.0	5.0	-	-	A4000+	-	-	-	1.0
010	IF	MIKDU	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
020	TF	TULSU	-	-	-16.0	4.2	-	-	A4000+	-	-	-	1.0
030	TF	RW03	-	-	-16.0	8.2	-	-	-	-	-3.9/49	-	-
040	CA	-	-	028 (043.6)	-16.0	-	-	-	A1700	-	-	-	1.0
050	DF	MIKDU	-	-	-16.0	-	-	R	-	-	-	-	1.0
060	HM	MIKDU	-	028 (043.6)	-16.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: MIKDU holding not included in standard APCH transitions.

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.000 MHZ	703558.70N 0294111.93E	GND STN, VHF Antenna