

ENSB RNP Z RWY 09 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NESAS	-	-	-10.0	-	-	-	A4100+	K230-	-	-	1.0
020	TF	LOLVO	-	-	-10.0	5.0	-	-	A4000+	K220-	-	-	1.0
010	IF	LALAD	-	-	-10.0	-	-	-	A4200+	K230-	-	-	1.0
020	TF	LOLVO	-	-	-10.0	5.0	-	-	A4000+	K220-	-	-	1.0
010	IF	OKDIT	-	-	-10.0	-	-	-	A4400+	-	-	-	1.0
020	TF	LOLVO	-	-	-10.0	5.0	-	-	A4000+	K220-	-	-	1.0
030	TF	SB605	-	-	-10.0	5.6	-	-	A3000+	-	-	-	1.0
040	TF	RW09	Y	-	-10.0	8.5	-	-	-	-	-3.2/50	-	0.3
050	DF	NESAS	-	-	-10.0	-	-	L	-	-	-	-	1.0
060	HM	NESAS	-	164 (174.2)	-10.0	1 MIN	-	R	A5000	K230-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.