

ENNA STAR RWY 16 (RNAV) - ROUTES

- GENERAL:

Surveillance service shall be available
- LOSS OF RNAV CAPABILITY:

Request vectoring.
- VECTORIZING:

Vectoring may be used for sequencing.
- RADIO COMMUNICATION FAILURE:

Squawk A7600. Proceed on STAR and make APCH to RWY 16

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
ABANU 1L (ABANU ONE LIMA ARRIVAL)	From ABANU to BAXIN.	Cross ABANU at or above FL110 Cross BAXIN at or above 4000 FT. MAX 230 KT IAS at BAXIN.	As cleared by ATC.	BAXIN.
LAPVI 1L (LAPVI ONE LIMA ARRIVAL)	From LAPVI to NEPKO.	Cross NEPKO at or above 4000 FT. MAX 230 KT IAS at NEPKO.	As cleared by ATC.	NEPKO.
LUVED 1L (LUVED ONE LIMA ARRIVAL)	From LUVED to NA410. To GUBEX.	Cross LUVED at or above FL120 Cross NA410 at or above 7000 FT. Cross GUBEX at or above 4000 FT. MAX 230 KT IAS at GUBEX.	As cleared by ATC.	GUBEX.