

ENHK GLS RWY 11 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ETNED	-	-	-12.0	-	-	-	A4400+	-	-	-	1.0
020	TF	HK502	-	-	-12.0	4.2	-	-	A2800+	-	-	-	1.0
010	IF	LURIV	-	-	-12.0	-	-	-	A4000+	-	-	-	1.0
020	TF	HK502	-	-	-12.0	4.2	-	-	A2800+	-	-	-	1.0
030	TF	HK501	-	-	-12.0	4.0	-	-	A2400+	-	-	-	1.0
040	TF	RW11	Y	-	-12.0	5.6	-	-	-	-	-3,9/49	-	-
050	CA	-	-	107 (118.8)	-12.0	-	-	-	A2000	-	-	-	1.0
060	DF	HK	-	-	-12.0	-	-	R	-	-	-	-	1.0
070	HM	HK	-	107 (118.8)	-12.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended RNAV procedure coding is based on ARINC 424-15 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.500 MHZ	702912.78N 0220832.60E	GND STN, VHF Antenna