

ENSB RNP W RWY 09 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	GELFO	-	-	-10.0	-	-	-	A5100+	-	-	-	0.7
020	TF	SB430	-	-	-10.0	6.0	-	-	A4000+	-	-	-	0.7
030	TF	SB431	-	-	-10.0	1.2	-	-	A3600+	-	-	-	0.4
040	RF	SB432	-	-	-10.0	8.3	-	R	A1200+	-	-	SB007 4.160	0.4
050	TF	RW09	Y	-	-10.0	3.2	-	-	-	-	-3.2/50	-	0.1
060	TF	SB423	-	-	-10.0	1.2	-	-	-	-	-	-	0.1
070	RF	SB424	-	-	-10.0	6.9	-	R	-	-	-	SB006 11.000	0.64
080	FA	SB424	-	132 (142.0)	-10.0	-	-	-	A3400+	-	-	-	1.0
090	DF	GELFO	-	-	-10.0	-	-	R	-	-	-	-	1.0
100	HM	GELFO	-	340 (350.3)	-10.0	1 MIN	-	L	A5100	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.