

ENKR RNP N RWY 05 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	MOMCO	-	-	-16.0	-	-	-	A4000+	-	-	-	1.0
20	TF	KR650	-	-	-16.0	2.0	-	-	A3200+	K220-	-	-	1.0
30	RF	KR651	-	-	-16.0	5.8	-	L	A1600+	K165-	-	KR003 2.650	1.0
40	TF	RW05	Y	-	-16.0	3.2	-	-	-	-	-3.8/50	-	0.3
50	TF	KR660	Y	-	-16.0	2.0	-	-	-	-	-	-	1.0
60	DF	DOGOD	-	-	-16.0	-	-	L	A3000	-	-	-	1.0
70	HM	DOGOD	-	143 (159.5)	-16.0	1 MIN	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.