

ENKR RNP W RWY 23 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	EVLOX	-	-	-16.0	-	-	-	A5000+	-	-	-	1.0
20	TF	KR601	-	-	-16.0	3.4	-	-	A4000+	K220-	-	-	0.8
10	IF	TEFPO	-	-	-16.0	-	-	-	A5000+	-	-	-	0.8
20	TF	KR600	-	-	-16.0	1.7	-	-	A4500+	K220-	-	-	0.8
30	RF	KR601	-	-	-16.0	1.7	-	R	A4000+	-	-	KR001 3.100	0.8
40	RF	KR602	-	-	-16.0	3.8	-	R	A3000+	-	-	KR002 2.810	0.8
50	RF	KR603	-	-	-16.0	4.3	-	R	A1600+	-	-	KR002 2.810	0.8
60	TF	RW23	Y	-	-16.0	3.5	-	-	-	-	-3.4/50	-	0.3
70	TF	KR507	Y	-	-16.0	6.8	-	-	-	-	-	-	1.0
80	DF	DOGOD	-	-	-16.0	-	-	R	A3000	-	-	-	1.0
90	HM	DOGOD	-	143 (159.5)	-16.0	1 MIN	-	L	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.