

ENOV RNP-B - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	EFMAF	-	-	-2.0	-	-	-	A4800+	-	-	-	1.0
020	TF	ISWAP	-	-	-2.0	5.0	-	-	A4000+	-	-	-	1.0
030	TF	OV300	-	-	-2.0	5.0	-	-	A3500+	-	-	-	1.0
010	IF	NIBOF	-	-	-2.0	-	-	-	A5800+	-	-	-	1.0
020	TF	ISWAP	-	-	-2.0	5.0	-	-	A4000+	-	-	-	1.0
030	TF	OV300	-	-	-2.0	5.0	-	-	A3500+	-	-	-	1.0
010	IF	ISWAP	-	-	-2.0	-	-	-	A4200+	-	-	-	1.0
020	TF	OV300	-	-	-2.0	5.0	-	-	A3500+	-	-	-	1.0
030	TF	OV301	Y	-	-2.0	5.2	-	-	-	-	-3.1/-	-	0.3
040	TF	OV302	Y	-	-2.0	3.7	-	-	-	-	-	-	1.0
050	DF	OV301	-	-	-2.0	-	-	L	-	-	-	-	1.0
060	TF	BVK	-	-	-2.0	6.5	-	-	-	-	-	-	1.0
070	HM	BVK	-	126 (127.9)	-2.0	1 MIN	-	L	A4600	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.