

## ENGM RNP E RWY 01R (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	LUVOX	-	-	-4.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	GM555	-	-	-4.0	5.4	-	-	A4000+	K200-	-	-	1.0
030	RF	GM681	-	-	-4.0	2.7	-	R	A3000+	-	-	GM011 3.100	0.3
040	RF	GM556	-	-	-4.0	1.6	-	R	A2500+	-	-	GM011 3.100	0.3
040	TF	GM557	-	-	-4.0	0.8	-	-	-	-	-	-	0.3
060	RF	GM558	-	-	-4.0	1.4	-	R	A1800+	-	-	GM010 3.000	0.3
070	TF	RW01R	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
080	TF	GM917	Y	-	-4.0	2.7	-	-	-	-	-	-	1.0
090	DF	NIDIM	Y	-	-4.0	-	-	R	A4000	-	-	-	1.0
100	DF	GRM	-	-	-4.0	-	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

## RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
GM010	600627.43N	0111020.95E
GM011	600539.55N	0111049.77E