

ENGM RNP O RWY 01L (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ERULO	-	-	-4.0	-	-	-	A5000+	K220-	-	-	0.8
20	TF	GM554	-	-	-4.0	6.8	-	-	A3500+	K210-	-	-	0.8
30	RF	GM551	-	-	-4.0	1.4	-	R	A3000+	-	-	GM007 3.400	0.3
40	TF	GM552	-	-	-4.0	1.9	-	-	A2400+	K205-	-	-	0.3
50	RF	GM553	-	-	-4.0	2.0	-	L	A1800+	-	-	GM006 3.000	0.3
60	TF	RW01L	-	-	-4.0	3.4	-	-	-	-	-3.0/50	-	0.3
70	TF	GM918	Y	-	-4.0	21.1	-	-	-	-	-	-	1.0
80	DF	GRM	-	-	-4.0	-	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

RF arc centre coordinates:

RF arc centre identifier	Latitude	Longitude
GM006	600839.82N	0105646.91E
GM007	600220.86N	0110100.33E