AIP NORGE / NORWAY

DE-ICING PLATFORM

COM
GND 126.180 MHZ
DE-ICE 121.705 MHZ
ATIS 119.080 MHZ

DE-ICE 121.705 MHZ
NORWAY

APRON DEICE "S"

TWR

118.655 MHZ

NOTES - REMARKS

TAXI ROUTE VIA "N1" TO "N" IS NORMALLY USED. WHEN DE-ICE POSITION "N" IS OCCUPIED BY PRECEEDING AIRCRAFT, WAIT IN DE-ICE SEQUENCING POSITION "N1" OR AS INSTRUCTED BY ATC.

TAXI ROUTE VIA "S1 TO "S" IS ONLY USED DURING PERIODS WITH STRONG SOUTHERLY WINDS. WHEN DE-ICE POSITION "S" IS OCCUPIED BY PRECEEDING AIRCRAFT, WAIT IN DE-ICE SEQUENCING POSITION "S1" OR AS INSTRUCTED BY ATC.

WHEN DE-ICING IS COMPLETED, CONTACT TWR FOR TAXI CLEARANCE.

USE OF TWY Y ALONG APRON DEICE IS LIMITED TO ACFT WITH CODE LETTER C OR SMALLER WHEN DE-ICING OF ACFT WITH CODE LETTER C TAKES PLACE. USE OF TWY Y ALONG APRON DEICE IS LIMITED TO ACFT WITH CODE LETTER B OR SMALLER WHEN DE-ICING OF ACFT WITH CODE LETTER D TAKES PLACE.

