

ENHV RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	EVTOM	-	-	-14.0	-	-	-	A4000+	-	-	-	1.0
020	TF	HV501	-	-	-14.0	4.0	-	-	A2500+	-	-	-	1.0
010	IF	OLJON	-	-	-14.0	-	-	-	A4000+	-	-	-	1.0
020	TF	HV501	-	-	-14.0	4.0	-	-	A2500+	-	-	-	1.0
030	TF	HV502	-	-	-14.0	3.5	-	-	A1800+	-	-	-	1.0
040	TF	HV503	Y	-	-14.0	3.0	-	-	-	-	-3.9/-	-	0.3
050	CA	-	-	176 (190)	-14.0	-	-	-	A2000	-	-	-	1.0
060	DF	EVTOM	-	-	-14.0	-	-	L	-	-	-	-	1.0
070	HM	EVTOM	-	266 (280.4)	-14.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.