

ENHV RNP-D - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAV AID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	EXCAD	-	-	-	-	-	-	A4000+	-	-	-	1.0
020	TF	HV701	-	-	-14°	4.0	-	-	A2500+	-	-	-	1.0
010	IF	SUPBO	-	-	-	-	-	-	A4000+	-	-	-	1.0
020	TF	HV701	-	-	-14°	4.0	-	-	A2500+	-	-	-	1.0
030	TF	HV702	-	-	-14°	3.5	-	-	A1800+	-	-	-	1.0
040	TF	HV703	Y	-	-14°	3.6	-	-	-	-	-3.9 / -	-	0.3
050	DF	EXCAD	-	-	-	-	-	L	-	-	-	-	1.0
060	HM	EXCAD	-	183 (196.6)	-14°	1 MIN	-	R	A4000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process