

ENAL RNP E RWY 06 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	AMSIC	-	-	-2.0	-	-	-	A7000+	-	-	-	1.0
020	TF	AL704	-	-	-2.0	4.5	-	-	A5800+	-	-	-	1.0
030	RF	AL703	-	-	-2.0	5.2	-	R	A4400+	-	-	AL001 12.0	1.0
040	TF	AL702	-	-	-2.0	4.9	-	-	A3100+	K240-	-	-	0.8
050	RF	AL701	-	-	-2.0	3.0	-	R	A2000+	-	-	AL002 3.2	0.3
060	RF	AL700	-	-	-2.0	2.7	-	R	-	-	-3.5	AL002 3.2	0.3
070	TF	RW06	Y	-	-2.0	2.5	-	-	-	-	-3.5/50	-	0.3
080	TF	AL822	-	-	-2.0	2.1	-	-	-	-	-	-	0.3
090	RF	AL705	-	-	-2.0	1.8	-	L	-	-	-	AL003 6.9	0.3
100	TF	AL821	-	-	-2.0	2.6	-	-	-	-	-	-	1.0
110	RF	AL706	-	-	-2.0	7.2	-	L	-	K220-	-	AL004 3.0	1.0
120	TF	TOMNO	-	-	-2.0	10.0	-	-	-	-	-	-	1.0
130	HM	TOMNO	-	328 (329.5)	-2.0	1 MIN	-	R	A5000+	K220-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.