

ENAL RNP N RWY 06 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	PUXME	-	-	-2.0	-	-	-	A5000+	-	-	-	1.0
020	TF	AL709	-	-	-2.0	4.0	-	-	A3500+	K220-	-	-	1.0
030	RF	AL708	-	-	-2.0	4.0	-	L	A2000+	-	-	AL006 2.8	1.0
040	RF	AL700	-	-	-2.0	2.7	-	L	-	-	-3.5	AL007 2.3	0.3
050	TF	RW06	Y	-	-2.0	2.5	-	-	-	-	-3.5/50	-	0.3
060	TF	AL822	-	-	-2.0	2.1	-	-	-	-	-	-	0.3
070	RF	AL705	-	-	-2.0	1.8	-	L	-	-	-	AL003 6.9	0.3
080	TF	AL821	-	-	-2.0	2.6	-	-	-	-	-	-	1.0
090	RF	AL706	-	-	-2.0	7.2	-	L	-	K220-	-	AL004 3.0	1.0
100	TF	TOMNO	-	-	-2.0	10.0	-	-	-	-	-	-	1.0
110	HM	TOMNO	-	328 (329.5)	-2.0	1 MIN	-	R	A5000+	K220-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.