ENSO STAR RWY 14/32 (RNAV) - ROUTES

GENERAL: Surveillance service shall be available

LOSS OF RNAV CAPABILITY: Request vectoring

VECTORING: Vectoring may be used for sequencing.

RADIO COMMUNICATION FAILURE: Squawk A7600. Proceed on STAR and make APCH to the assigned runway.

RWY 14

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
REVTA 1L	From REVTA to SO460, to	Cross REVTA at or above FL100.	As cleared by	NATGA HLDG
	SO450 to NATGA.	Cross SO460 at or above 8000FT	ATC.	
(REVTA		Cross SO450 at or above 6000 FT.		
ONE LIMA ARRIVAL)		Cross NATGA at or above 4000 FT.		Į.

RWY 32

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
REVTA 1M	From REVTA to SO560, to	Cross REVTA at or above FL100.	As cleared by	ARVOG HLDG
	SO550, to ARVOG.	Cross SO560 at or above 8000 FT.	ATC.	
(REVTA		Cross SO550 at or above 6000 FT.		
ONE MIKE ARRIVAL)		Cross ARVOG at or above 4500 FT.		

Avinor 04 SEP 2025