

ENCN RNP W RWY 03 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	BIFCO	-	-	-3.0	-	-	-	A3500+	-	-	-	1.0
020	TF	CN826	-	-	-3.0	2.7	-	-	A3000+	-	-	-	1.0
030	TF	CN825	-	-	-3.0	2.2	-	-	A2400+	-	-	-	0.6
040	TF	CN824	-	-	-3.0	1.8	-	-	A1900+	-	-	-	0.6
050	RF	CN823	-	-	-3.0	2.9	-	L	-	-	-3.5	CN842 1.9	0.3
060	TF	RW03	Y	-	-3.0	1.9	-	-	-	-	-3.5/50	-	0.3
070	TF	NELIP	-	-	-3.0	13.0	-	-	A3000+	-	-	-	1.0
080	HM	NELIP	-	212 (215.1)	-3.0	1 MIN	-	R	A3000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.