AERODROME CHART ICAO

ARP 585236N 0053816E
AD ELEV 30

STAVANGER, SOLA
NORWAY

NOTES - REMARKS

- APCH LGT RWY 10: XBAR AT 150 M. INTERVALS OF 30 M. INNERMOST LGT 30 M FM THR. SEQUENCED FLG LGT ON CL. LED.
- APCH LGT RWY 28: XBAR AT 600, 450 AND 300 M. INTERVALS OF 30 M. INNERMOST LGT 30 M FM THR. LED.
- APCH LGT RWY 18: XBAR AT 450, 300 AND 150 M. INTERVALS OF 30 M. INNERMOST LGT 30 M FM THR. SEQUENCED FLG LGT ON CL.
- APCH LGT RWY 36: XBAR AT 600, 450, 300 AND 150 M. INTERVALS OF 30 M. INNERMOST LGT 30 M FH THR.

Runway strength, REF AD 2.12
Apron surface and strength, REF AD 2.8
Taxiway width, surface and strength, REF AD 2.8
Declared distances, REF AD 2.13

RUNWAY

RWY	BRG
10	104.69
28	284.72
18	177.51
36	357.51

COM

ATIS	126.005 MHZ
DEICE	121.955 MHZ
DEICE	131.755 MHZ
GND	121.755 MHZ
TWR	279.050 MHZ
TWR	118.355 MHZ



CHANGES: NEW HOTSPOT.