

ENBN RNP 085 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ARNOR	-	-	-5.0	-	-	-	A1500+	-	-	-	1.0
20	TF	VEGAS	-	-	-5.0	5.8	-	-	A1500+	-	-	-	1.0
30	TF	ELPUM	-	-	-5.0	4.0	-	-	A1500+	-	-	-	1.0
40	TF	BURAL	-	-	-5.0	2.0	-	-	A1500+	-	-	-	1.0
50	TF	BN410	Y	-	-5.0	3.0	-	-	-	-	-3.3/-	-	0.3
60	DF	ELPUM	-	-	-5.0	-	-	L	A1500	-	-	-	1.0
70	HM	ELPUM	-	085 (090.0)	-5.0	1 MIN	-	L	A1500	K100-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: ELPUM holding not included in standard APCH transitions.