

ENSD RNP RWY 08 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ETNEK	-	-	-2.0	-	-	-	A6700+	-	-	-	1.0
020	TF	KUVOV	-	-	-2.0	4.0	-	-	A5800+	-	-	-	1.0
010	IF	OKPAS	-	-	-2.0	-	-	-	A6600+	-	-	-	1.0
020	TF	KUVOV	-	-	-2.0	4.0	-	-	A5800+	-	-	-	1.0
010	IF	KUVOV	-	-	-2.0	-	-	-	A5800+	-	-	-	1.0
020	TF	GIRER	-	-	-2.0	3.9	-	-	A5000+	-	-	-	1.0
030	TF	SD400	Y	-	-2.0	6.0	-	-	-	-	-4.5/50	-	0.3
040	TF	SD401	Y	-	-2.0	7.4	-	-	-	-	-	-	1.0
050	VI	-	-	262 (264.4)	-2.0	-	-	L	-	-	-	-	1.0
060	CF	KUVOV	-	292 (294.4)	-2.0	-	FLO	-	A5800	-	-	-	1.0
070	HM	KUVOV	-	112 (114.2)	-2.0	1 MIN	-	L	A5800	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: KUVOV holding not included in standard APCH transitions.