

ENBR RNP 043- RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ELMEG	-	-	-1.0	-	-	-	A2000+	-	-	-	1.0
020	TF	BR711	-	-	-1.0	4.7	-	-	A2000+	-	-	-	1.0
010	IF	VIKSO	-	-	-1.0	-	-	-	A2100+	-	-	-	1.0
020	TF	MOMUX	-	-	-1.0	1.6	-	-	A2100+	-	-	-	1.0
030	TF	BR711	-	-	-1.0	2.0	-	-	A2000+	-	-	-	1.0
040	TF	BR710	Y	-	-1.0	3.9	-	-	-	-	-	-	0.3
050	FA	BR710	Y	043 (043.9)	-1.0	-	FLS	-	A680	-	-	-	1.0
060	CF	BR715	-	314 (314.5)	-1.0	-	FLS	L	A2000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.