

## ENFL RNP-D - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	RIKDU	-	-	-1.0	-	-	-	A5400+	-	-	-	1.0
020	TF	UNBOG	-	-	-1.0	5.0	-	-	A5400+	-	-	-	1.0
010	IF	APSUS	-	-	-1.0	-	-	-	A5400+	-	-	-	1.0
020	TF	UNBOG	-	-	-1.0	5.0	-	-	A5400+	-	-	-	1.0
010	IF	ESATO	-	-	-1.0	-	-	-	A5600+	-	-	-	1.0
020	TF	UNBOG	-	-	-1.0	5.0	-	-	A5400+	-	-	-	1.0
030	TF	FL501	-	-	-1.0	5.0	-	-	A3200+	-	-	-	1.0
040	TF	FL500	Y	-	-1.0	6.0	-	-	-	-	-4.2/50	-	0.3
050	DF	GOSLI	-	-	-1.0	-	-	L	-	-	-	-	1.0
060	HM	GOSLI	-	099 (099.7)	-1.0	4.0*	-	L	A4000	K140-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

\*4.0 NM FM GOSLI

Note: UNBOG holding not included in standard APCH transitions