

ENFL RNP RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	PETED	-	-	-1.0	-	-	-	A5700+	-	-	-	1.0
020	TF	VAXEM	-	-	-1.0	3.5	-	-	A5000+	K170-	-	-	1.0
010	IF	IDBIB	-	-	-1.0	-	-	-	A5400+	-	-	-	1.0
020	TF	VAXEM	-	-	-1.0	3.5	-	-	A5000+	K170-	-	-	1.0
030	TF	LEKBU	-	-	-1.0	2.8	-	-	A4000+	-	-	-	1.0
040	TF	FL710	Y	-	-1.0	9.0	-	-	-	-	-3.8/50	-	0.3
050	DF	GOSLI	-	-	-1.0	-	-	-	-	K140-	-	-	1.0
060	HM	GOSLI	-	099 (099.7)	-1.0	4.0*	-	L	A4000	K140-	-	-	1.0

*4.0 NM FM GOSLI

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: VAXEM holding not included in standard APCH transitions