

ENBL RNP Z RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	REPRI	-	-	-2.0	-	-	-	A6600+	-	-	-	1.0
020	TF	INGOS	-	-	-2.0	5.0	-	-	A6500+	-	-	-	1.0
010	IF	LELPO	-	-	-2.0	-	-	-	A6500+	-	-	-	1.0
020	TF	INGOS	-	-	-2.0	5.0	-	-	A6500+	-	-	-	1.0
010	IF	INDUX	-	-	-2.0	-	-	-	A7100+	-	-	-	1.0
020	TF	INGOS	-	-	-2.0	5.0	-	-	A6500+	-	-	-	1.0
030	TF	XIBUR	-	-	-2.0	3.6	-	-	A6000+	-	-	-	1.0
040	TF	BL400	Y	-	-2.0	7.8	-	-	-	-	-4.6/50	-	0.3
050	CA	-	-	252 (253.9)	-2.0	-	FLO	-	A2500	-	-	-	1.0
060	DF	BL403	-	-	-2.0	-	-	-	-	-	-	-	1.0
070	TF	IDONI	-	-	-2.0	9.4	-	-	-	-	-	-	1.0
080	HM	IDONI	-	342 (343.5)	-2.0	1 MIN	-	L	A5500	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: INGOS holding not included in standard APCH transitions.