

ENHD RNP X RWY 13 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	INRIX	-	-	-1.0	-	-	-	A4000+	-	-	-	1.0
020	TF	HD417	-	-	-1.0	15.2	-	-	A4000+	-	-	-	1.0
030	TF	HD416	-	-	-1.0	5.0	-	-	A4000	-	-	-	1.0
040	TF	HD415	-	-	-1.0	5.2	-	-	-	-	-3.0	-	0.3
050	RF	HD400	-	-	-1.0	5.4	-	L	-	-	-3.0	HD001 r=2.550	0.3
060	TF	RW13	Y	-	-1.0	1.6	-	-	-	-	-3.0/50	-	0.3
070	TF	RIVNU	-	-	-1.0	6.2	-	-	-	-	-	-	1.0
080	HM	RIVNU	-	313 (314.4)	-1.0	1 MIN	-	L	A2500	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.