

ENVR RNP 197 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ROSAP	-	-	-6.0	-	-	-	A1500+	-	-	-	1.0
20	TF	VR630	-	-	-6.0	3.0	-	-	A1500+	-	-	-	1.0
30	TF	VR640	-	-	-6.0	3.0	-	L	A1500+	-	-	-	1.0
40	TF	VR650	-	-	-6.0	2.2	-	-	-	-	-3.7/-	-	0.3
50	TF	VR660	Y	-	-6.0	0.75	-	-	-	-	-	-	0.3
60	TF	VR670	-	-	-6.0	3.7	-	-	-	-	-	-	1.0
70	TF	VR770	-	-	-6.0	6.6	-	L	-	-	-	-	1.0
80	TF	VEXIM	-	-	-6.0	3.0	-	L	A1200	-	-	-	1.0
90	HM	VEXIM	-	264 (270.0)	-6.0	1 MIN	-	R	A1200	K110-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.