

ENST RNP Y RWY 02 (LPV only) - RECOMMENDED CODING

| SN | PD | WI    | Fly-over | °M (°T)        | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/ TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|----|----|-------|----------|----------------|---------|-----------|------------|----|----------|------------|-------------------|------------------------|----------|
| 10 | IF | PATTO | -        | -              | -5.0    | -         | -          | -  | A4600+   | -          | -                 | -                      | 1.0      |
| 20 | TF | ST416 | -        | -              | -5.0    | 5.0       | -          | -  | A3000+   | -          | -                 | -                      | 1.0      |
| 10 | IF | SEGKA | -        | -              | -5.0    | -         | -          | -  | A5000+   | -          | -                 | -                      | 1.0      |
| 20 | TF | ST416 | -        | -              | -5.0    | 5.0       | -          | -  | A3000+   | -          | -                 | -                      | 1.0      |
| 10 | IF | ROPBE | -        | -              | -5.0    | -         | -          | -  | A5000+   | -          | -                 | -                      | 1.0      |
| 20 | TF | ST416 | -        | -              | -5.0    | 5.0       | -          | -  | A3000+   | -          | -                 | -                      | 1.0      |
| 30 | TF | ST415 | -        | -              | -5.0    | 4.5       | -          | -  | A2000+   | -          | -                 | -                      | 1.0      |
| 40 | TF | RW02  | Y        | -              | -5.0    | 5.9       | -          | -  | -        | -          | -3.0/50           | -                      | -        |
| 50 | TF | ST425 | Y        | -              | -5.0    | 11.5      | -          | -  | -        | -          | -                 | -                      | 0.3      |
| 60 | DF | UGMAL | -        | -              | -5.0    | -         | -          | L  | -        | -          | -                 | -                      | 1.0      |
| 70 | HM | UGMAL | -        | 265<br>(269.9) | -5.0    | 1 MIN     | -          | R  | A5000    | -          | -                 | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 200 FT shall not be used due to approach operation Type B limitations.

FAS DB

|                                 |                                       |                              |               |
|---------------------------------|---------------------------------------|------------------------------|---------------|
| Operation type                  | 0                                     | LTP/FTP ellipsoidal height   | 46.2          |
| SBAS provider                   | 1                                     | FPAP latitude                | 655759.8545N  |
| Airport identifier              | ENST                                  | FPAP longitude               | 0122848.1660E |
| Runway                          | RW02                                  | Threshold crossing height    | 50            |
| Approach performance designator | 0                                     | TCH units                    | FT            |
| Route indicator                 | Y                                     | Glide path angle             | 3.0           |
| Reference path data selector    | 0                                     | Course width at threshold    | 105           |
| Reference path identifier       | E02A                                  | Length offset                | 336           |
| LTP/FTP latitude                | 655710.1740N                          | Horizontal alert limit (HAL) | 40            |
| LTP/FTP longitude               | 0122751.9035E                         | Vertical alert limit (VAL)   | 35            |
|                                 |                                       |                              |               |
|                                 | PRECISION APPROACH PATH CRC REMAINDER |                              | 1524A043      |