

ENAT RNP-B - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	PUWIL	-	-	-12.0	-	-	-	A4900+	-	-	-	1.0
20	TF	EMFUN	-	-	-12.0	3.2	-	-	A4000+	-	-	-	1.0
10	IF	YERME	-	-	-12.0	-	-	-	A4800+	-	-	-	1.0
20	TF	EMFUN	-	-	-12.0	3.2	-	-	A4000+	-	-	-	1.0
10	IF	EMFUN	-	-	-12.0	-	-	-	A4400+	-	-	-	1.0
20	TF	AT408	-	-	-12.0	3.2	-	-	A4000+	-	-	-	1.0
30	TF	AT409	Y	-	-12.0	9.6	-	-	-	-	-3.3	-	0.3
40	DF	AT415	Y	-	-12.0	-	-	R	-	-	-	-	1.0
50	DF	OMOMO	-	-	-12.0	-	-	R	-	-	-	-	1.0
60	HM	OMOMO	-	265 (276.7)	-12.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.