

ENSD RNP RWY 26 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	OGDIT	-	-	-2.0	-	-	-	A6800+	-	-	-	1.0
020	TF	ITVAK	-	-	-2.0	4.0	-	-	A6800+	-	-	-	1.0
010	IF	GIGMU	-	-	-2.0	-	-	-	A6800+	-	-	-	1.0
020	TF	ITVAK	-	-	-2.0	4.0	-	-	A6800+	-	-	-	1.0
010	IF	ITVAK	-	-	-2.0	-	-	-	A6800+	-	-	-	1.0
020	TF	NUNKI	-	-	-2.0	3.8	-	-	A6000+	-	-	-	1.0
030	TF	SD500	Y	-	-2.0	9.2	-	-	-	-	-5.4/50	-	0.3
040	FA	SD500	-	292 (294.0)	-2.0	-	-	-	A4000	K130-	-	-	1.0
050	DF	OGDIT	-	-	-2.0	-	-	R	-	-	-	-	1.0
060	HM	OGDIT	-	348 (350.0)	-2.0	1 MIN	-	L	A8000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.