

ENZV RNP 044 (CAT H) - RECOMMENDED CODING

-	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/FHPCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	IGSUF	-	-	-2.0	-	-	-	A1300+	-	-	-	1.0
20	TF	ZV447	-	-	-2.0	3.0	-	-	A1300+	-	-	-	1.0
30	TF	NOVDE	-	-	-2.0	3.0	-	-	A1100+	-	-	-	1.0
40	TF	ZV469	Y	-	-2.0	1.6	-	-	-	-	-3.4/50	-	0.3
50	TF	ZV449	Y	-	-2.0	1.3	-	-	-	-	-	-	1.0
60	DF	ZV450	-	-	-2.0	-	-	L	A1400	-	-	-	1.0
70	TF	RUSSE	-	-	-2.0	13.7	-	-	A1400	-	-	-	1.0
80	HM	RUSSE	-	294 (296.1)	-2.0	1MIN	-	L	A1400	K120-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

FAS DB

Operation type	0	LTP/FTP ellipsoidal height	136.1
SBAS provider	1	FPAP latitude	585235.2700N
Airport identifier	ENZV	FPAP longitude	0053852.4380E
Runway	04	Threshold crossing height	50
Approach performance designator	0	TCH units	FT
Route indicator	-	Glide path angle	3.4
Reference path data selector	0	Course width at threshold	105
Reference path identifier	E04A	Length offset	0
LTP/FTP latitude	585134.8710N	Horizontal alert limit (HAL)	40
LTP/FTP longitude	0053651.2800E	Vertical alert limit (VAL)	35
		PRECISION APPROACH PATH CRC REMAINDER	B74F4554