

ENBL GLS RWY 07 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	SUVEN	-	-	-2.0	-	-	-	A5500+	-	-	-	1.0
020	TF	ESEKI	-	-	-2.0	5.0	-	-	A5500+	-	-	-	1.0
010	IF	IDONI	-	-	-2.0	-	-	-	A5500+	-	-	-	1.0
020	TF	ESEKI	-	-	-2.0	5.0	-	-	A5500+	-	-	-	1.0
010	IF	ESEKI	-	-	-2.0	-	-	-	A5500+	-	-	-	1.0
020	TF	MOMAN	-	-	-2.0	4.0	-	-	A5300+	-	-	-	1.0
030	TF	RW07	Y	-	-2.0	10.0	-	-	-	-	-3.9/49	-	-
040	TF	BL503	Y	-	-2.0	6.2	-	-	-	K130-	-	-	1.0
050	DF	IDONI	-	-	-2.0	-	-	L	A5500	-	-	-	1.0
060	HM	IDONI	-	342 (343.5)	-2.0	1 MIN	-	L	A5500	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
113.500 MHZ	612342.18N 0054536.75E	GND STN, VHF Antenna