

ENBL GLS RWY 25 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	REPRI	-	-	-2.0	-	-	-	A6600+	-	-	-	1.0
020	TF	INGOS	-	-	-2.0	5.0	-	-	A6500+	-	-	-	1.0
010	IF	LELPO	-	-	-2.0	-	-	-	A6500+	-	-	-	1.0
020	TF	INGOS	-	-	-2.0	5.0	-	-	A6500+	-	-	-	1.0
010	IF	INDUX	-	-	-2.0	-	-	-	A7100+	-	-	-	1.0
020	TF	INGOS	-	-	-2.0	5.0	-	-	A6500+	-	-	-	1.0
030	TF	XIBUR	-	-	-2.0	3.6	-	-	A6000+	-	-	-	1.0
040	TF	RW25	Y	-	-2.0	10.1	-	-	-	-	-4.5/49	-	-
050	TF	MOMAN	-	-	-2.0	10.5	-	-	A4000+	-	-	-	1.0
060	FA	MOMAN	-	252 (253.5)	-2.0	-	-	-	A4000+	-	-	-	1.0
070	DF	MOMAN	-	-	-2.0	-	-	L	A6000+	-	-	-	1.0
080	HM	MOMAN	-	072 (073.5)	-2.0	1 MIN	-	R	A6000+	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: INGOS holding not included in standard APCH transitions.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
113.500 MHZ	612342.18N 0054536.75E	GND STN, VHF Antenna