

ENBN GLS RWY 03 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ABRAK	-	-	-5.0	-	-	-	A3700+	-	-	-	1.0
20	TF	BN420	-	-	-5.0	5.6	-	-	A2500+	-	-	-	1.0
10	IF	GITAP	-	-	-5.0	-	-	-	A3700+	-	-	-	1.0
20	TF	BN420	-	-	-5.0	4.5	-	-	A2500+	-	-	-	1.0
10	IF	MEDEK	-	-	-5.0	-	-	-	A4600+	-	-	-	1.0
20	TF	BN420	-	-	-5.0	4.4	-	-	A2500+	-	-	-	1.0
30	TF	BN421	-	-	-5.0	3.5	-	-	A1900+	-	-	-	1.0
40	TF	FTP	Y	-	-5.0	5.8	-	-	-	-	-3.0/49	-	-
50	CA	-	-	030 (035.1)	-5.0	-	BNN	-	A600	K130-	-	-	1.0
60	CF	PEPIB	-	347 (351.8)	-5.0	-	BNN	L	-	-	-	-	1.0
70	FA	-	-	347 (351.8)	-5.0	-	BNN	-	A2600	-	-	-	1.0
80	DF	PEPIB	-	-	-5.0	-	-	L	-	-	-	-	1.0
90	HM	PEPIB	-	167 (171.8)	-5.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
114.050 MHZ	652739.35N 0121312.37E	GND STN, VHF Antenna