

## ENMS GLS RWY 33 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ASLUB	-	-	-6.0	-	-	-	A5800+	-	-	-	1.0
020	TF	ELSOT	-	-	-6.0	5.0	-	-	A5800+	-	-	-	1.0
010	IF	EKRIN	-	-	-6.0	-	-	-	A6700+	-	-	-	1.0
020	TF	ELSOT	-	-	-6.0	5.0	-	-	A5800+	-	-	-	1.0
010	IF	XAREN	-	-	-6.0	-	-	-	A6200+	-	-	-	1.0
020	TF	ELSOT	-	-	-6.0	5.0	-	-	A5800+	-	-	-	1.0
030	TF	MS700	-	-	-6.0	4.2	-	-	A4000+	-	-	-	1.0
040	TF	FTP	-	-	-6.0	8.8	-	-	-	-	-3.9/49	-	-
050	CF	MS705	-	008 (014.0)	-6.0	-	-	-	-	-	-	-	1.0
060	TF	MS706	-	-	-6.0	5.0	-	-	-	-	-	-	1.0
070	TF	ELSOT	-	-	-6.0	15.7	-	-	-	-	-	-	1.0
080	HM	ELSOT	-	339 (345.0)	-6.0	1 MIN	-	R	A5800	-	-	-	1.0

**Warning:** TF leg between MS700 and FTP is solely to establish a FAT. The GLS procedure is an ILS equivalent where the first leg of the missed approach is intended to be a turn as soon as practicable, intercepting the CF leg to MS705 with the associated restrictions on when the turn may be initiated.

Note: ELSOT holding not included in standard APCH transitions.

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

## SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.500 MHZ	654657.26N 0131305.98E	GND STN, VHF Antenna