

ENSK GLS RWY 08 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	SK534	-	-	-7.0	-	-	-	A5200+	-	-	-	1.0
020	TF	UDANU	-	-	-7.0	5.0	-	-	A4000+	-	-	-	1.0
030	TF	SK532	-	-	-7.0	4.0	-	-	A3500+	-	-	-	1.0
040	TF	RW08	Y	-	-7.0	8.2	-	-	-	-	-3.9/49	-	-
050	CA	-	Y	084 (091.0)	-7.0	-	-	-	A1000	-	-	-	1.0
060	CF	KG	-	050 (057.2)	-7.0	-	-	L	-	-	-	-	1.0
070	FA	KG	-	050 (057.0)	-7.0	-	-	-	A3300	-	-	-	1.0
080	DF	KG	-	-	-7.0	-	-	L	-	-	-	-	1.0
090	HM	KG	-	234 (241.0)	-7.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
115.700 MHZ	683455.24N 0150128.24E	GND STN, VHF Antenna