

ENST GLS RWY 02 - RECOMMENDED CODING

| SN | PD | WI    | Fly-over | °M (°T)     | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|----|----|-------|----------|-------------|---------|-----------|------------|----|----------|------------|------------------|------------------------|----------|
| 10 | IF | PATTO | -        | -           | -5.0    | -         | -          | -  | A4600+   | -          | -                | -                      | 1.0      |
| 20 | TF | ST416 | -        | -           | -5.0    | 5.0       | -          | -  | A3000+   | -          | -                | -                      | 1.0      |
| 10 | IF | SEGKA | -        | -           | -5.0    | -         | -          | -  | A5000+   | -          | -                | -                      | 1.0      |
| 20 | TF | ST416 | -        | -           | -5.0    | 5.0       | -          | -  | A3000+   | -          | -                | -                      | 1.0      |
| 10 | IF | ROPBE | -        | -           | -5.0    | -         | -          | -  | A5000+   | -          | -                | -                      | 1.0      |
| 20 | TF | ST416 | -        | -           | -5.0    | 5.0       | -          | -  | A3000+   | -          | -                | -                      | 1.0      |
| 30 | TF | ST415 | -        | -           | -5.0    | 4.5       | -          | -  | A2000+   | -          | -                | -                      | 1.0      |
| 40 | TF | RW02  | Y        | -           | -5.0    | 5.9       | -          | -  | -        | -          | -3.0/49          | -                      | -        |
| 50 | CA | -     | -        | 020 (024.7) | -       | -         | -          | -  | A2700+   | -          | -                | -                      | 1.0      |
| 60 | DF | UGMAL | -        | -           | -5.0    | -         | -          | L  | -        | -          | -                | -                      | 1.0      |
| 70 | HM | UGMAL | -        | 265 (269.9) | -5.0    | 1 MIN     | -          | R  | A5000    | -          | -                | -                      | 1.0      |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

| FREQUENCY   | POSITION                  | REMARK                  |
|-------------|---------------------------|-------------------------|
| 114.300 MHZ | 655722.00N<br>0122812.61E | GND STN, VHF<br>Antenna |