

ENSS GLS RWY 15 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NILIP	-	-	-17.0	-	-	-	A4000+	-	-	-	1.0
020	TF	AGLOB	-	-	-17.0	5.0	-	-	A2000+	-	-	-	1.0
030	TF	SS806	-	-	-17.0	4.0	-	-	A2000+	-	-	-	1.0
040	TF	RW15	Y	-	-17.0	4.6	-	-	-	-	-3.9/49	-	-
050	CA	-	-	146 (163.2)	-17.0	-	-	-	A1500+	-	-	-	1.0
060	DF	NILIP	-	-	-17.0	-	-	R	-	-	-	-	1.0
070	HM	NILIP	-	056 (072.9)	-17.0	1 MIN	-	L	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
116.200 MHZ	702110.56N 0310239.45E	GND STN, VHF Antenna