

ENSG RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	BAXEP	-	-	-2.0	-	-	-	A6500+	-	-	-	1.0
020	TF	OGUTI	-	-	-2.0	4.4	-	-	A6500+	-	-	-	1.0
010	IF	ERLIX	-	-	-2.0	-	-	-	A6500+	-	-	-	1.0
020	TF	OGUTI	-	-	-2.0	5.8	-	-	A6500+	K130-	-	-	1.0
010	IF	OGUTI	-	-	-2.0	-	-	-	A6500+	-	-	-	1.0
020	TF	SG410	-	-	-2.0	3.1	-	-	A6000+	-	-	-	1.0
030	TF	SG411	Y	-	-2.0	8.2	-	-	-	-	-	-	0.3
040	TF	SG412	Y	-	-2.0	9.5	-	-	-	-	-	-	1.0
060	DF	ERLIX	-	-	-2.0	-	-	R	A7500	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: OGUTI holding not included in standard APCH transitions.