

ENRS GLS RWY 02 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	DIVOL	-	-	-5.0	-	-	-	A4000+	-	-	-	1.0
20	TF	RS404	-	-	-5.0	5.0	-	-	A2000+	-	-	-	1.0
10	IF	RS406	-	-	-5.0	-	-	-	A4000+	-	-	-	1.0
20	TF	RS404	-	-	-5.0	5.0	-	-	A2000+	-	-	-	1.0
10	IF	RS404	-	-	-5.0	-	-	-	A2000+	-	-	-	1.0
20	TF	RS403	-	-	-5.0	4.5	-	-	A2000+	-	-	-	1.0
30	TF	RW02	Y	-	-5.0	4.7	-	-	-	-	-3.9/49	-	-
40	CA	-	-	024 (028.6)	-5.0	-	-	-	A1000+	-	-	-	1.0
50	DF	DIVOL	-	-	-5.0	-	-	R	-	-	-	-	1.0
60	HM	DIVOL	-	204 (208.9)	-5.0	1 MIN	-	R	A4000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

SCAT-I FREQUENCY AND POSITION

FREQUENCY	POSITION	REMARK
116.100 MHZ	673133.02N 0120617.35E	GND STN, VHF Antenna