

ENZV RNP S RWY 18 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	POLXA	-	-	-2.0	-	-	-	A3000+	K220-	-	-	0.7
20	TF	ZV117	-	-	-2.0	1.5	-	-	A2300+	-	-	-	0.7
30	RF	ZV118	-	-	-2.0	2.4	-	L	A2000+	-	-	ZV005 2.900	0.7
40	RF	ZV119	-	-	-2.0	2.1	-	L	A1700+	-	-	ZV005 2.900	0.7
50	RF	ZV115	-	-	-2.0	1.4	-	L	A1500+	-	-	ZV004 4.700	0.7
60	RF	ZV116	-	-	-2.0	1.1	-	L	-	-	-3.0	ZV004 4.700	0.3
70	TF	RW18	Y	-	-2.0	3.4	-	-	-	-	-3.0/50	-	0.3
80	TF	YOFUF	-	-	-2.0	15.0	-	-	-	-	-	-	1.0
90	HM	YOFUF	-	177 (179.1)	-2.0	1 MIN	-	R	A3000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.