

ENZV RNP O RWY 36 (AR) - RECOMMENDED CODING

| SN | PD | WI | Fly-over | °M (°T) | MAG VAR | DIST (NM) | REC NAVAID | TD | ALT (FT) | Speed (KT) | VPA (°)/ TCH (FT) | ARC CENTRE RADIUS (NM) | RNP (NM) |
|----|----|-------|----------|----------------|---------|-----------|------------|----|----------|------------|-------------------|------------------------|----------|
| 10 | IF | UNIDE | - | - | -2.0 | - | - | - | A3000+ | K220- | - | - | 1.0 |
| 20 | TF | ZV334 | - | - | -2.0 | 3.9 | - | - | A2000+ | - | - | - | 1.0 |
| 30 | RF | ZV332 | - | - | -2.0 | 2.2 | - | R | A1500+ | - | - | ZV008 3.500 | 1.0 |
| 40 | RF | ZV333 | - | - | -2.0 | 2.4 | - | L | - | - | -3.0 | ZV007 2.800 | 0.3 |
| 50 | TF | RW36 | Y | - | -2.0 | 2.1 | - | - | - | - | -3.0/50 | - | 0.3 |
| 60 | TF | EGOKE | - | - | -2.0 | 15.0 | - | - | - | - | - | - | 1.0 |
| 70 | HM | EGOKE | - | 357 (359.1) | -2.0 | 1 MIN | - | L | A3000 | - | - | - | 1.0 |

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.