

## ENEV RNP W RWY 35 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	MELLE	-	-	-8.0	-	-	-	A5000+	-	-	-	1.0
020	TF	EV726	-	-	-8.0	6.2	-	-	A3500+	-	-	-	1.0
030	TF	EV725	-	-	-8.0	4.2	-	-	A2000+	K175-	-	-	0.4
040	RF	EV720	-	-	-8.0	2.8	-	L	-	-	-3.4	EV009 1.75	0.3
050	TF	RW35	Y	-	-8.0	2.4	-	-	-	-	-3.4/50	-	0.3
060	TF	OKNOT	-	-	-8.0	7.2	-	-	-	-	-	-	1.0
070	FA	OKNOT	-	350 (357.6)	-8.0	-	-	-	A3900+	-	-	-	1.0
080	DF	OKNOT	-	-	-8.0	-	-	L	-	-	-	-	1.0
090	HM	OKNOT	-	170 (177.6)	-8.0	1 MIN	-	R	A5000	K220-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.