

## ENSK RNP Z RWY 26 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ONOWE	-	-	-7	-	-	-	A5200+	-	-	-	1.0
020	TF	SK555	-	-	-7	5.0	-	-	A3600+	-	-	-	1.0
010	IF	ABIVE	-	-	-7	-	-	-	A5200+	-	-	-	1.0
020	TF	SK555	-	-	-7	5.0	-	-	A3600+	-	-	-	1.0
010	IF	FUGGU	-	-	-7	-	-	-	A4800+	-	-	-	1.0
020	TF	SK555	-	-	-7	5.0	-	-	A3600+	-	-	-	1.0
030	TF	SK556	-	-	-7	4.9	-	-	A2000+	-	-	-	1.0
040	TF	SK557	Y	-	-7	4.8	-	-	-	K120-	-3.0/-	-	0.3
050	DF	SK558	Y	-	-7	-	-	L	-	K130-	-	-	1.0
060	DF	SK556	-	-	-7	-	-	L	-	-	-	-	1.0
070	TF	FUGGU	-	-	-7	7.0	-	-	-	-	-	-	1.0
080	HM	FUGGU	-	144 (151)	-7	1 MIN	-	L	A3600	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.