

ENAL RNP E RWY 24 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	ARJAN	-	-	-2.0	-	-	-	A5000+	-	-	-	0.5
020	TF	AL712	-	-	-2.0	5.0	-	-	A3400+	K190-	-	-	0.5
030	RF	AL711	-	-	-2.0	5.3	-	L	A1700+	-	-	AL008 2.1	0.5
040	RF	AL710	-	-	-2.0	1.6	-	R	-	-	-3.0	AL009 1.96	0.3
050	TF	RW24	Y	-	-2.0	3.5	-	-	-	-	-3.0/50	-	0.3
060	TF	ATBOL	Y	-	-2.0	9.0	-	-	-	-	-	-	1.0
070	DF	TOMNO	-	-	-2.0	-	-	R	-	-	-	-	1.0
080	HM	TOMNO	-	328 (329.5)	-2.0	1 MIN	-	R	A5000+	K220-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.