

## ENTIC RNP Z RWY 18 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	NONRU	-	-	-10.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	OGBOD	-	-	-10.0	6.0	-	-	A5000+	K200-	-	-	1.0
010	IF	APSIM	-	-	-10.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	OGBOD	-	-	-10.0	6.0	-	-	A5000+	K200-	-	-	1.0
010	IF	OGBOD	-	-	-10.0	-	-	-	A5000+	K200-	-	-	1.0
020	TF	BAXAS	-	-	-10.0	4.9	-	-	A4500+	-	-	-	1.0
030	TF	TCS04	Y	-	-10.0	9.6	-	-	-	-	-4.0/50	-	0.3
040	TF	TCS05	Y	-	-10.0	7.0	-	-	-	-	-	-	1.0
050	TF	TCS06	Y	-	-10.0	13.7	-	-	-	K250-	-	-	1.0
060	DF	ETUTU	-	-	-10.0	-	-	R	-	-	-	-	1.0
070	HM	ETUTU	-	003 (012.9)	-10.0	1 MIN	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: BAXAS holding not included in standard APCH transitions.