

## ENTC RNP Z RWY 36 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	REBLI	-	-	-10.0	-	-	-	A5000+	K220-	-	-	1.0
020	TF	VAMEN	-	-	-10.0	6.0	-	-	A5000+	K200-	-	-	1.0
010	IF	UMSEG	-	-	-10.0	-	-	-	A6000+	K220-	-	-	1.0
020	TF	VAMEN	-	-	-10.0	6.0	-	-	A5000+	K200-	-	-	1.0
010	IF	VAMEN	-	-	-10.0	-	-	-	A5000+	K200-	-	-	1.0
020	TF	ETUTU	-	-	-10.0	4.0	-	-	A5000+	-	-	-	1.0
030	TF	TC406	Y	-	-10.0	10.6	-	-	-	-	-4.0/50	-	0.3
040	TF	TC407	-	-	-10.0	11.0	-	-	-	-	-	-	1.0
050	TF	TC408	-	-	-10.0	7.1	-	L	-	-	-	-	1.0
060	TF	OSRAD	-	-	-10.0	11.1	-	-	A5000	K230-	-	-	1.0
070	HM	OSRAD	-	196 (206.0)	-10.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: ETUTU holding not included in standard APCH transitions.