

ENEV STAR RWY 35 (RNAV) - ROUTES

GENERAL:	Surveillance service shall be available
LOSS OF RNAV CAPABILITY:	Request vectoring
VECTORING:	Vectoring may be used for sequencing.
RADIO COMMUNICATION FAILURE:	Squawk A7600. Proceed on STAR and make APCH to RWY 35

DESIGNATOR	ROUTE	RESTRICTIONS	DESCEND	CLEARANCE LIMIT
ELDUR 1M (ELDUR ONE MIKE ARRIVAL)	From ELDUR to VEGEN, to MAXED.	Cross MAXED at or above 7000 FT.	As cleared by ATC.	MAXED
EVANI 3M (EVANI THREE MIKE ARRIVAL)	From EVANI to LEGLU.	Cross LEGLU at or above 7000 FT.	As cleared by ATC.	LEGLU
GILEN 1M (GILEN ONE MIKE ARRIVAL)	From GILEN to EV750, to MAXED	Cross GILEN at or above FL 120. Cross EV750 at or above 9100 FT. Cross MAXED at or above 7000 FT.	As cleared by ATC.	MAXED
MUGIF 1M (MUGIF ONE MIKE ARRIVAL)	From MUGIF to UNZOK to LEGLU	Cross LEGLU at or above 7000 FT	As cleared by ATC.	LEGLU
OSKUB 1M (OSKUB ONE MIKE ARRIVAL)	From OSKUB to VEGEN, to MAXED.	Cross OSKUB at or above FL 120. Cross MAXED at or above 7000 FT.	As cleared by ATC.	MAXED
PENNO 1M (PENNO ONE MIKE ARRIVAL)	From PENNO to STETI.	Cross PENNO at or above 8000 FT. Cross STETI at or above 7000 FT.	As cleared by ATC.	STETI