

ENAN RNP X RWY 32 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	RUTOD	-	-	-8.0	-	-	-	A3600+	-	-	-	1.0
020	TF	IPLUR	-	-	-8.0	5.0	-	-	A2500+	-	-	-	1.0
010	IF	GEVPI	-	-	-8.0	-	-	-	A4300+	-	-	-	1.0
020	TF	IPLUR	-	-	-8.0	5.0	-	-	A2500+	-	-	-	1.0
010	IF	IVGAM	-	-	-8.0	-	-	-	A4400+	-	-	-	1.0
020	TF	IPLUR	-	-	-8.0	5.0	-	-	A2500+	-	-	-	1.0
030	TF	AN710	-	-	-8.0	5.7	-	-	A1500+	-	-	-	1.0
040	TF	AN700	Y	-	-8.0	4.5	-	-	-	-	-3.0/50	-	0.3
050	TF	ROBUM	-	-	-8.0	9.8	-	-	-	-	-	-	1.0
060	HM	ROBUM	-	142 (150.0)	-8.0	1 MIN	-	L	A2000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.