

ENTC RNP-A - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M(°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA(°)/ TCH(FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	PAXLO	-	-	-10.0	-	-	-	A5000+	-	-	-	1.0
020	TF	XEGRO	-	-	-10.0	8.2	-	-	A5000+	-	-	-	1.0
030	TF	NIPOS	-	-	-10.0	6.0	-	-	A3800+	-	-	-	1.0
040	TF	TC802	-	-	-10.0	3.6	-	-	A3800+	-	-	-	1.0
050	TF	TC801	Y	-	-10.0	7.1	-	-	-	-	-4.0/-	-	0.3
060	CF	TC505	Y	183 (193.0)	-10.0	-	-	-	-	-	-	-	1.0
070	TF	TC506	Y	-	-10.0	13.7	-	-	-	-	-	-	1.0
080	DF	ETUTU	-	-	-10.0	-	-	R	A5000	-	-	-	1.0
090	HM	ETUTU	-	003 (012.9)	-10.0	1 MIN	-	L	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.