

ENEV RNP W RWY 17 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/ TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	CONGE	-	-	-8.0	-	-	-	A5000+	-	-	-	0.3
020	TF	EV524	-	-	-8.0	6.2	-	-	A3500+	K210-	-	-	0.3
030	RF	EV523	-	-	-8.0	2.5	-	R	A2500+	-	-	EV004 2.61	0.3
040	RF	EV520	-	-	-8.0	2.5	-	R	A1500+	-	-	EV005 2.37	0.3
050	TF	RW17	Y	-	-8.0	3.5	-	-	-	-	-3.7/50	-	0.3
060	TF	EV525	-	-	-8.0	1.6	-	-	-	-	-	-	1.0
070	RF	EV526	-	-	-8.0	5.9	-	R	-	K255-	-	EV006 3.915	1.0
080	TF	ACCID	-	-	-8.0	8.7	-	-	-	-	-	-	1.0
090	HM	ACCID	-	⁰⁶⁶ (074.0)	-8.0	1 MIN	-	R	A5000	K205-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.